

US007219744B2

(12) United States Patent

Pietras

(10) Patent No.: US 7,219,744 B2

(45) **Date of Patent:** May 22, 2007

(54) METHOD AND APPARATUS FOR CONNECTING TUBULARS USING A TOP DRIVE

- (75) Inventor: Bernd-Georg Pietras, Wedemark (DE)
- (73) Assignee: Weatherford/Lamb, Inc., Houston, TX
 - (US)
- (*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35 U.S.C. 154(b) by 54 days.

- (21) Appl. No.: 11/288,976
- (22) Filed: Nov. 29, 2005

(65) Prior Publication Data

US 2006/0124316 A1 Jun. 15, 2006

Related U.S. Application Data

(63) Continuation of application No. 10/738,950, filed on Dec. 17, 2003, now Pat. No. 7,021,374, which is a continuation of application No. 10/354,226, filed on Jan. 29, 2003, now Pat. No. 6,688,398, which is a continuation of application No. 09/762,698, filed as application No. PCT/GB99/02704 on Aug. 16, 1999, now Pat. No. 6,527,047.

(30) Foreign Application Priority Data

Aug. 24, 1998 (GB) 9818366.8

- (51) Int. Cl. *E21B 19/06*
 - **E21B 19/06** (2006.01) **U.S. Cl.** **166/379**; 166/77.51

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

122,514 A 1/1872 Bullock 1,077,772 A 11/1913 Weathersby

1,185,582 A	5/1916	Bigneti
1,301,285 A	4/1919	Leonard
1,342,424 A	6/1920	Cotten
1,418,766 A	6/1922	Wilson
1,471,526 A	10/1923	Pickin
1,585,069 A	5/1926	Youle
1,728,136 A	9/1929	Power
1,777,592 A	10/1930	Thomas
1,825,026 A	9/1931	Thomas
1,830,625 A	11/1931	Schrock
1,880,218 A	10/1932	Simmons
1,917,135 A	7/1933	Littell
1,981,525 A	11/1934	Price

(Continued)

FOREIGN PATENT DOCUMENTS

CA 2 335 192 11/2001

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 10/189,570, filed Jun. 6, 2002.

(Continued)

Primary Examiner—Frank S. Tsay (74) Attorney, Agent, or Firm—Patterson & Sheridan, LLP

(57) ABSTRACT

An apparatus for facilitating the connection of tubulars, said apparatus comprising a winch, at least one wire line, and a device for gripping the tubular, the arrangement being such that, in use, the winch can be used to winch said at least one wire and said device to position a tubular below said top drive.

31 Claims, 9 Drawing Sheets

